

Declaration of Performance

MR1 Monocouche One Coat Render



Declaration of Performance Number: CPR – 275/02

- 01 Unique identification code of the product-type: Ecorend MR1 Monocouche One Coat Render
- 02 Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4): **Batch Number: See product packaging**
- 03 Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification: **Internal and external rendering on walls**
- 04 Name, registered trade name or registered trade mark and contact address of the manufacturer as set in article 11 (5): **La Roc, Dalton Industrial Estate, Dalton, Thirsk, North Yorkshire YO7 3HE**
- 05 Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2): **Not Relevant**
- 06 System or systems for assessment and verification of constancy of performance of the construction product in accordance with annex V: **System 2+**
- 07 In the case of declaration of performance concerning a construction product covered by a harmonised standard: **EN 998-1:2010 Specification for mortar for masonry Part 1: Rendering and plastering mortar**
- 08 In the case of declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not Relevant**
- 09 Declared performance

Reaction to fire	Class A1
Dry bulk density	1650 kg/m ³
Compressive strength	CS IV
Adhesion	≥ 1.0 N/mm ² , (FP) B
Adhesion after weathering cycles	≥ 0.4 N/mm ² , (FP) B
Water permeability after weathering cycles	≤ 1ml/cm ² after 48h
Capillary water absorption	W2
Water vapour permeability coefficient	μ ≤ 15/35 (EN 1745 Table A.12)
Thermal conductivity	(λ10, dry) 0.61 W/mK (EN 1745 Table A.12 mean value; P = 50%)
- 10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance of point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

CE MARKING ACCORDING TO CPR 305/2011 AND EN 998-1:2010

	
La Roc Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE 14	
Ecorend MR1 Monocouche Render One Coat OC: One coat rendering mortar for external use EN 998-1:2010	
Reaction to fire	Class A1
Dry bulk density	1650 kg/m ³
Compressive strength	CS IV
Adhesion	≥ 1.0 N/mm ² , (FP) B
Adhesion after weathering cycles	≥ 0.4 N/mm ² , (FP) B
Water permeability after weathering cycles	≤ 1ml/cm ² after 48h
Capillary water absorption	W2
Water vapour permeability coefficient	μ ≤ 15/35
Thermal conductivity	(λ10, dry) 0.61 W/mK (tab. mean value; P = 50%)

Signed for and on behalf of the manufacturer by:
 Gavin Bagshaw – Technical Information & Customer Support Lead



Place and date of issue:
 12th September 2018 - Dalton/Thirsk