

G10 Multi-Surface Primer

Technical Data

Pack Size
20kg Tub

Coverage
Approx. 40-60m² per
20kg

Humidity Requirement
Less than 85%

Finishing Tool
Brush, Long Pile Roller
or Spray

Application Temperature
5°C - 25°C for a minimum
of 24 hours

Suitable Substrate
Rough new and old brick
and block substrates

Dilution Rate
Do not dilute



**Polymer
Technology**



Ready To Use



**Excellent
Adhesion**



**Water
Based**



Description

Ecorend G10 Multi-Surface Primer is a polymer resin based primer, specifically designed for use on high suction substrates where suction control is required. This primer is engineered with fine particle polymers, ensuring deep penetration into the substrate and creating ultra-high adhesion. The sandy texture creates a good key for subsequent topcoats and the colouring allows for better visibility on which areas have been primed, making application easier.

Preparation

Ensure the substrate is clean, dry and free from any material which may impair adhesion. Clean with XR1 Fungicidal Wash if required.

Application

Mix the product before use.

For ease of application the product can be diluted by up to 10% with clean water.

Apply in one light coat either by brush, roller or spray application.

Note: Before application of render coat test the substrate for suction i.e. using clean water, splash some water on the primed surface. The water should sit on the surface and then be sucked into the primer after approximately one minute.

If the water is instantly sucked in, **then another light coat of primer will be required.**

Note: Excessive application, too much primer, is not recommended. This will eliminate all suction and can potentially lead to drying or application issues of the render coat. It is recommended to apply a render test panel to assess the suction in the substrate after priming before applying to a full elevation.

The render product can be applied as soon as the G10 Multi-Surface Primer is dry, i.e. after 1 to 24 hours depending on weather conditions.

Storage

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

Tool Cleaning

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

Health & Safety Instructions

G10 Multi-Surface Primer

Contains a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one and 2-methyl-2h-isothiazol-3-one. May produce an allergic reaction. If medical advice is needed, have product container or label to hand. Contains CMIT/MIT as a biocidal product for in-can preservation purposes only.

LOW VOC CONTENT: 3g/ltr

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

Important Information

DO NOT apply if frost is forecast within 24 hours, in wet conditions, in temperatures below 5°C or above 25°C, to elevations in direct sunlight or to substrates that are hot. Coverage rates are approx. and do not take into account wastage and uneven substrates.