



**NON-COMBUSTIBLE
INSULATION**


PRODUCT DESCRIPTION

Rocksilk® EWI Slab is a high performance non-combustible Rock Mineral Wool slab manufactured with a water-repellent additive, and is designed for use in External Wall Insulation (EWI) systems.

It is non-combustible with the best possible Euroclass A1 reaction to fire classification.

BENEFITS

- EWI systems made with non-combustible materials remove the need for separate fire breaks.
- Provides additional acoustic performance to the external wall.
- Breathable, allowing moisture vapour to pass through the construction removing the risk of condensation.
- Suitable for use with both silicone and mineral render systems providing design and installation flexibility.
- Easy to cut with a large bladed knife or serrated saw.



APPLICATION

- External Wall Insulation (see page 60)

CERTIFICATION



SPECIFICATIONS

ROCKSILK® EWI SLAB							
Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (mm)	Width (mm)	Pieces per pallet	Area per pallet (m ²)	Pallet product code
120	0.036	3.30	1200	600	20	14.400	271217
110	0.036	3.05	1200	600	20	14.400	271267
100	0.036	2.75	1200	600	24	17.280	264383
90	0.036	2.50	1200	600	24	17.280	264382

All dimensions are nominal.

Available via approved contractors.



Fire: Euroclass reaction to fire classification | Sustainability: Generic BRE Green Guide rating

